

## Alpha Olefin C1214

Alpha olefin C1214, a blend of 1-Docecene and 1-Tetradecene, is produced by Ineos Oligomers by using a modified Ziegler ethylene chain growth technology. The mixture is a clear water white, mobile liquid at room temperature.

## **Applications**

Alpha Olefin C1214 enters into all reactions typical of alpha olefins. C1214 can be used in the production of amines and amine oxides, oxo alcohols, alkylated aromatics, epoxides and synthetic fatty acids.

## Typical Properties<sup>1</sup>

Typical Properties	
Carbon Number, wt% (by GC)	
C10	<1
C12	66
C14	33
C16	<u>&lt;1</u>
	100
Hydrocarbon Type, wt% (by GC)	
Monoolefin	99.7
Paraffin	0.3
	100.0
Olefin Isomers, mole% by (NMR)	
Linear terminal	86.5
Branched terminal	9.5
Linear internal	_ 4.0
	100.0
Other Properties	
Color, APHA	10
Density at 20 ℃, g/mL	0.762
Density at 68°F, lbs/gal	6.36
Pour Point, ℃	-35
Flash Point, ℃, (ASTM D 56)	81
Boiling Range, °C, (5%-95%)	217-250

<sup>&</sup>lt;sup>1</sup>Typical properties will vary within specification limits.

## **Transportation Mode**

Alpha olefin C1214 is stored under a nitrogen blanket. It is not corrosive to steel or aluminum. Contact with air, water or oxygen should be avoided because olefins are sensitive to moisture and auto-oxidation which form impurities that can interface with subsequent reactions. Olefins should be handled under a dry, inert gas atmosphere. As with all hydrocarbons, olefins can form explosive mixtures with air or oxygen in certain concentrations.

Alpha Olefin C1214 is available in rail tank cars, tank trailers, marine vessels and isotanks. Alpha Olefin C1214 is available in drums on special order.

Technical information contained herein is furnished without charge or obligation, and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, INEOS makes no representation about, and is not responsible or liable for the accuracy or reliability of data, nor for toxicological effects or Industrial Hygiene requirements associated with particular uses of any product described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item not supplied by INEOS. The "Properties" and "Applications" listed in this document are not specifications. They are provided as information only and in no way modify, amend, enlarge, or create any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED.