LL6930AA

Product Technical Information

LL6930AA is a linear low density polyethylene copolymer containing hexene (C6) as the co-monomer.

Benefits & Features

- Very high stiffness
- Excellent overall film appearance and surface finish
- Good balance between stiffness and puncture resistance

Applications

LL6930AA is a high rigidity cast film grade suitable as an anti-cling layer in co-extruded stretch-film structures and for hygienic film.

If corona treatment is necessary, the level should normally be in the range 38-48 mN/m.

We recommend that you consult your INEOS O&P Europe technical representative for further advice on the use of **LL6930AA**.

| Properties | Conditions | Test Methods | Values | Units |
|-------------------------------|--------------|--------------|--------|----------|
| Rheological | | | | |
| Melt Flow Rate | 190°C/2.16kg | ISO 1133-1 | 3.5 | g/10min |
| Physical | | | | |
| Density ISO 17855-1 | 23°C | ISO 1183-1 | 936 | kg/m^3 |
| Mechanical* | | | | |
| Dart drop impact Method A | | ASTM D 1709 | 50 | g |
| Tensile strain at break | | ISO 527-3 | 55 | MPa |
| Elongation at break | | ISO 1184 | 600 | 0/0 |
| 1% Secant modulus | | ISO 1184 | 300 | MPa |
| Elmendorf tear strength MD/TD | 40°C | ASTM D 1922 | 30/40 | g/25µm |
| Optical* | | | | |
| Haze | | ASTM D 1003 | 5 | 0/0 |
| Gloss | 45° | ASTM D 2457 | 80 | ‰ |
| | | | | |

Additives

Antioxidants

Data should not be used for specification work

Extrusion conditions

LL6930AA can be processed on most standard extrusion equipment. Optimisation may be required depending on the exact end use requirements.

For best cast film performance, **LL6930AA** should be processed on machinery purpose designed for LLDPE. Particular attention should be paid to controlling melt temperature, and to ensuring that casting conditions are optimal. Melt temperatures in the range 240 - 280°C are normally used.

September, 2019
Published by

INEOS Olefins & Polymers Europe

^{*20}µm film, 150m/min line speed, 260°C melt temperature - MD = machine direction TD = transverse direction

LL6930AA

Storage

The product should be stored in a dry and dust free environment at temperature below 50°C. Exposure to direct sunlight should be avoided as this may lead to product deterioration. It is advised to process the product within maximum one year after delivery.

Regulatory Information

The product and uses described herein may be subject to specific requirements or limitations for use in certain applications like food contact, drinking water or medical devices. Further information may be obtained from the website www.ineos.com where a specific Regulatory Certificate is available for each grade under the heading "SDS & Regulatory Certificate".

Unless specifically indicated, the product mentioned herein is not suitable for applications in the medical or pharmaceutical sectors.

Health and Safety Information

The product described herein may require precautions in handling. The available product health and safety information for this material is contained in the Safety Data Sheet (SDS) that may be obtained from the website www.ineos.com. Before using any material, a customer is advised to consult the SDS for the product under consideration for use.

Exclusion of Liability

Although INEOS O&P Europe endeavours to ensure that all information and advice relating to our materials or other materials howsoever provided to you by INEOS O&P Europe is accurate and up to date, no representation or warranty, express or implied is made by INEOS O&P Europe as to its accuracy or completeness. All such information and advice is provided in good faith and INEOS O&P Europe is not, to the maximum extent permitted by law, liable for any action you may take as a result of relying on such information or advice or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

In addition data and numerical results howsoever provided to you by INEOS O&P Europe are given in good faith and are general in nature. Data and numerical results are not and shall not be regarded as specifications and as such INEOS O&P Europe is not, to the maximum extent permitted by law, liable for any action that you take as a result of relying on such data and results or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

It remains at all times your responsibility to ensure that INEOS O&P Europe materials are suitable for the particular purpose intended and INEOS O&P Europe shall not be responsible for any loss or damage caused by misuse of INEOS O&P Europe products. To the maximum extent permitted by law, INEOS O&P Europe accepts no liability whatsoever arising out of the application, adaptation or processing of the products described herein, the use of other materials in lieu of INEOS O&P Europe materials or the use of INEOS O&P Europe materials in conjunction with such other materials.

Published by INEOS Olefins & Polymers Europe