



ELTEX® MED PH21G630

Product Technical Information

Low Density Polyethylene for Pharmaceutical Blow Moulding

Benefits & Features

ELTEX® MED PH21G630 is a LD-polyethylene produced in a high-pressure process intended for blow moulding of soft and flexible packages for pharmaceutical products. It is produced according to good manufacturing practice and is additive-free.

Applications

ELTEX® MED PH21G630 can be used in “blow-fill and seal” machines for the production of ampoules. The product can also be used for pharmaceutical products manufactured with other conversion techniques such as injection blow-moulding, injection moulding and film blowing.

The product is not intended for heat sterilization.

Properties	Conditions	Test Methods	Values	Units
Physical				
Density		ISO1183-1 & ISO 1872-1	921	kg/m ³
Melt Flow Rate	190°C/2.16 kg	ISO 1133-1	1.5	g/10 min
Mechanical				
Tensile Stress at Yield	50 mm/min	ISO 527-1,-2	11	MPa
Thermal				
DSC Melting Point	10°C/min	INEOS test Method	110	°C
Data should not be used for specification work				

Compliance to Regulations on Medical use

ELTEX® MED PH21G630 complies with the European Pharmacopoeia – Monograph 3.1.4, USP <88> Class VI and USP 661.1

Processing guidelines

ELTEX® MED PH21G630 is easy to extrude.
Recommended melt temperature is 165-190°C

Storage

The product should be stored in a dry and dust free environment at temperature below 50°C. Exposure to direct sunlight should be avoided as this may lead to product deterioration. It is advised to process the product within maximum one year after delivery.



ELTEX[®] MED PH21G630

Regulatory Information

The product and uses described herein may be subject to specific requirements or limitations for use in certain applications like food contact, drinking water or medical devices. Further information may be obtained from the website www.ineos.com where a specific Regulatory Certificate is available for each grade under the heading "SDS & Regulatory Certificate".

Health and Safety Information

The product described herein may require precautions in handling. The available product health and safety information for this material is contained in the Safety Data Sheet (SDS) that may be obtained from the website www.ineos.com. Before using any material, a customer is advised to consult the SDS for the product under consideration for use.

Exclusion of Liability

Although INEOS O&P Europe endeavours to ensure that all information and advice relating to our materials or other materials howsoever provided to you by INEOS O&P Europe is accurate and up to date, no representation or warranty, express or implied is made by INEOS O&P Europe as to its accuracy or completeness. All such information and advice is provided in good faith and INEOS O&P Europe is not, to the maximum extent permitted by law, liable for any action you may take as a result of relying on such information or advice or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

In addition data and numerical results howsoever provided to you by INEOS O&P Europe are given in good faith and are general in nature. Data and numerical results are not and shall not be regarded as specifications and as such INEOS O&P Europe is not, to the maximum extent permitted by law, liable for any action that you take as a result of relying on such data and results or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

It remains at all times your responsibility to ensure that INEOS O&P Europe materials are suitable for the particular purpose intended and INEOS O&P Europe shall not be responsible for any loss or damage caused by misuse of INEOS O&P Europe products. To the maximum extent permitted by law, INEOS O&P Europe accepts no liability whatsoever arising out of the application, adaptation or processing of the products described herein, the use of other materials in lieu of INEOS O&P Europe materials or the use of INEOS O&P Europe materials in conjunction with such other materials.