

# TUB121NTW

POLYETHYLENE COPOLYMER

## TECHNICAL DATASHEET

### Product Description

TUB121NTW is a natural bimodal HDPE grade designed for extrusion of large diameter, thick wall piping for potable water, industrial and mining applications. When blended with an approved black concentrate, the resulting formulation<sup>1</sup> is listed in PPI TR-4 as PE4710 and PE100 and is certified to NSF/ANSI Standard 14, CSA B137.1 and CSA B137.4.

### Typical Properties<sup>2</sup>

Property	English Units	SI Units	ASTM Method
<b>Resin</b>			
Density		0.949 g/cc	D4883
Melt Index (190°C/5.0 kg)		0.25 g/10 min	D1238
Melt Index (190°C/21.6 kg)		8.0 g/10 min	D1238
<b>Compression Molded Specimens</b>			
Tensile Strength @ Yield	3,500 psi	24 MPa	D638
Tensile Elongation @ Break	>600 %	>600 %	D638
Flexural Modulus, 2% Secant Method	130,000 psi	900 MPa	D790A
Brittleness Temperature	<-180 °F	<-118 °C	D746
Notch Tensile (PENT)	>10,000 hrs	>10,000 hrs	F1473
Cell Classification	445574C <sup>3</sup>	445574C <sup>3</sup>	D3350
<b>Pipe<sup>3</sup></b>			
Hydrostatic Design Basis (HDB) @ 23°C (73°F) @ 60°C (140°F)	1,600 psi 1,000 psi	11 MPa 6.9 MPa	D2837
Minimum Required Strength (MRS)	---	10 MPa	ISO 9080
Oxidative Resistance Classification	CC3	CC3	D3350
Rapid Crack Propagation Resistance (0°C) <sup>4</sup> S4 Critical Pressure (P <sub>c, S4</sub> ) Full Scale Critical Pressure (P <sub>c, FS</sub> ) <sup>5</sup>	>145 psig >560 psig	>10 bar >38.6 bar	ISO 13477

<sup>1</sup> Under compound name TUB121

<sup>2</sup> Typical properties will vary and are not to be used for specifications.

<sup>3</sup> Pipe extruded from blend of TUB121N with approved black concentrate. Contact INEOS Technical Service for a list of approved concentrates

<sup>4</sup> Pipe Size: 24-in diameter, SDR 11

<sup>5</sup> Calculated per ISO 13477 correlation factor:  $P_{c,FS,bar} = 3.6P_{c,S4,bar} + 2.6$

# TUB121NTW

POLYETHYLENE COPOLYMER

## TECHNICAL DATASHEET

### Regulatory Information

The product and uses described herein may require global product registrations and notifications for chemical inventory listings, or for use in food contact or medical devices. For further information, please refer to the Regulatory Position Statement (RPS) online at [www.ineos-op.com](http://www.ineos-op.com), or call + 1-800-527-5419.

### Health and Safety Information

The product described herein may require precautions in handling and use because of toxicity, flammability, or other consideration. The Safety Data Sheet (SDS) contains the available product health and safety information for this material and can be found at [www.ineos-op.com](http://www.ineos-op.com). Before using any material, a customer is advised to consult the SDS for the product under consideration for use.

The Safety Data Sheet for this product contains shipping descriptions and should be consulted, before transportation, as a reference in determining the proper shipping description. If the material shipped by INEOS O&P is altered or modified, different shipping descriptions may apply and the SDS of the original material should not be used.

All information contained herein, whether technical or otherwise, is furnished without charge or obligation and is given and accepted at recipient's sole risk. As conditions of use may vary and are beyond the control of INEOS Olefins & Polymers USA, no representations or warranties, express or implied, are made with respect to the accuracy, reliability, or completeness of this information. This information in no way modifies, amends, enlarges, or creates any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXCLUDED. INEOS Olefins & Polymers USA will not be responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices, or from hazards inherent in the nature of the product and/or material, nor for toxicological effects or Industrial Hygiene associated with particular use of any product described herein. This information relates only to the specific product and/or material designated and may not be valid for such product and/or material used in combination with any other product and/or material or in any process, unless otherwise specified. This information will not be construed as a recommendation for any use that may infringe any patent, trademark, or the like, or as an endorsement of any material, equipment, service, or other item not supplied by INEOS Olefins & Polymers USA.

The name and logo INEOS are trademarks of the INEOS Group and its affiliated companies and businesses.