



# ELTEX<sup>®</sup> PF6030XA

## Product Technical Information

ELTEX<sup>®</sup> PF6030XA is a polyethylene copolymer containing hexene-1 as comonomer produced with a metallocene catalyst.

## Benefits & Features

ELTEX<sup>®</sup> PF6030XA offers the following properties:

- High stretchability in cast film applications
- High holding force
- Excellent web stability during extrusion
- High output rates
- Excellent overall film appearance and surface finish
- Very high puncture resistance

## Applications

ELTEX<sup>®</sup> PF6030XA is particularly suitable for high performance cast stretch film applications in co-extruded structures as well as for other advanced polyolefin films produced with cast extrusion process.

We recommend that you consult your INEOS technical representative for further advice on the use of ELTEX<sup>®</sup> PF6030XA.

Properties	Conditions	Test Methods	Values	Units
<b>Rheological</b>				
Melt Flow Rate	190°C/2.16kg	ISO 1133-1	3.0	g/10min
<b>Physical</b>				
Density ISO 17855-1	23°C	ISO 1183-1	912	kg/m <sup>3</sup>
<b>Mechanical*</b>				
Dart drop impact Method A		ASTM D 1709	>800	g
Puncture Resistance, energy		INEOS Test Method	6.8	J
Tensile strength at break MD/TD		ISO 527-3	42/32	MPa
Tensile strain at break MD/TD		ISO 527-3	280/400	%
1% Secant modulus MD/TD		ISO 527-3	105/100	MPa
Elmendorf tear strength MD/TD		ASTM D 1922	270/400	g/25mm
<b>Optical*</b>				
Haze	20µm	ASTM D 1003	1	%
Gloss	45°	ASTM D 2457	93	% <sub>00</sub>

**Data should not be used for specification work**

\* 20 µm film, 230°C melt temperature – MD = machine direction, TD = transverse direction



# ELTEX<sup>®</sup> PF6030XA

## Processing guidelines

ELTEX<sup>®</sup> PF6030XA should be processed on machinery purpose designed for LLDPE. The product is well stabilized, melt temperatures in the range 230 – 280°C can be used.

## Storage

The product should be stored in a dry and dust free environment at temperature below 50°C. Exposure to direct sunlight should be avoided as this may lead to product deterioration.

It is advised to process the product within maximum one year after delivery.

---

### Regulatory Information

The product and uses described herein may be subject to specific requirements or limitations for use in certain applications like food contact, drinking water or medical devices. Further information may be obtained from the website [www.ineos.com](http://www.ineos.com) where a specific Regulatory Certificate is available for each grade under the heading "SDS & Regulatory Certificate".

Unless specifically indicated, the product mentioned herein is not suitable for applications in the medical or pharmaceutical sectors.

### Health and Safety Information

The product described herein may require precautions in handling. The available product health and safety information for this material is contained in the Safety Data Sheet (SDS) that may be obtained from the website [www.ineos.com](http://www.ineos.com). Before using any material, a customer is advised to consult the SDS for the product under consideration for use.

### Exclusion of Liability

Although INEOS O&P Europe endeavours to ensure that all information and advice relating to our materials or other materials howsoever provided to you by INEOS O&P Europe is accurate and up to date, no representation or warranty, express or implied is made by INEOS O&P Europe as to its accuracy or completeness. All such information and advice is provided in good faith and INEOS O&P Europe is not, to the maximum extent permitted by law, liable for any action you may take as a result of relying on such information or advice or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

In addition data and numerical results howsoever provided to you by INEOS O&P Europe are given in good faith and are general in nature. Data and numerical results are not and shall not be regarded as specifications and as such INEOS O&P Europe is not, to the maximum extent permitted by law, liable for any action that you take as a result of relying on such data and results or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

It remains at all times your responsibility to ensure that INEOS O&P Europe materials are suitable for the particular purpose intended and INEOS O&P Europe shall not be responsible for any loss or damage caused by misuse of INEOS O&P Europe products. To the maximum extent permitted by law, INEOS O&P Europe accepts no liability whatsoever arising out of the application, adaptation or processing of the products described herein, the use of other materials in lieu of INEOS O&P Europe materials or the use of INEOS O&P Europe materials in conjunction with such other materials.

April, 2019

Published by

**INEOS** Olefins & Polymers Europe