# AME<sup>™</sup> 6001 PREMIUM MARINE RESINS

For decades, INEOS Composites' products have served the best boat builders in the world with new technologies that deliver unmatched quality and performance. Our newest product continues that tradition by capturing the latest trends and addressing the needs of today's high-performance boats.

AME™ premium marine resins have been the preferred and trusted resins for the most respected boat builders for more than 30 years. As one of the first premium resins ever designed for the marine industry, AME™ resins have a flawless record of providing long lasting performance that has yet to be equaled. Designed in collaboration with leading boat builders, these modified epoxy vinyl ester resins have been designed exclusively to address today's performance and production needs. INEOS has exceeded industry expectations across North America and Europe with a history of being the market leader and developing products that deliver reliable, durable, real world performance.

The AME<sup>TM</sup>6001 resin is a 100% modified epoxy vinyl ester resin. This resin has superior physical properties to stand up to the high performance demands of the marine environment. The large number of flex fatigue cycles demonstrates how the AME<sup>TM</sup>6001 can take a pounding without fear of failure. The high heat distortion temperature (HDT) ensures great long term cosmetics even with dark colors.

## **Typical Property Comparison**

Property	AME™ 6001 Series	Standard Marine General Purpose Resin	Unit	Test Method
Tensile Strength	11,500	6,400	psi	ISO 527
Tensile Modulus	500	490	ksi	ISO 527
Tensile Elongation	5.2	2.3	%	ISO 527
Flexural Strength	21,600	12,000	psi	ISO 178
Flexural Modulus	525	500	ksi	ISO 178
Flexural Fatigue	125,135	20,953	cycles	
Ultimate HDT	111	87	°C	ISO 75

### **Benefits**

- Excellent physical properties
- Over 5% tensile elongation
- Ultimate HDT of 232 °F
- Greatest resistance to fatigue failure
- User friendly processing
- Fast wet-out
- Minimal air entrapment
- Excellent surface quality
- Outstanding blister resistance
- Exceeds ISO 12215-1 Type A and DNV Grade 1 mechanical properties



## Innovation and Collaboration to Grow the Marine Market

INEOS has designed a complete line of premium gelcoats, epoxy vinyl ester resins, unsaturated polyester resins, low profile resins, fuel tank resins and barrier coats. Combined with INEOS's boat building expertise, product development and technical service, INEOS will help you become a better, more profitable boat builder.

INEOS's technical service team has an industry leading reputation for solving problems. We work closely with our customers to understand specific application challenges and recommend the best product to meet business objectives. Whether focused on product design, process optimization or new product development, INEOS prides itself on building partnerships that lead to innovative solutions. Visit ineos.com/composites to learn more.

# **GLOBAL PRESENCE**

# Global Headquarters INEOS Composites

North America Dublin, OH USA

Dublin, OH USA Tel: +1 614 790 9299 Americascustomer.composites@INEOS.com

### **Regional Centers**

Asia Pacific

Shanghai, P.R. China Tel: +86 21 2402 4688 ASIAcustomer.composites@INEOS.com

Europe

Barcelona, Spain Tel: +34 93 206 5120 EMEAcustomer.composites@INEOS.com

### India

Navi Mumbai Tel: +91 22 6148 9696 EMEAcustomer.composites@INEOS.com

### Latin America

Tel: +55 11 4136 6477
Americascustomer.composites@INEOS.com

- ® Registered trademark, INEOS or its subsidiaries, registered in various countries
- $\ensuremath{^{\text{TM}}}$  Trademark, INEOS or its subsidiaries, registered in various countries
- © 2019, INEOS / COM19-13039.3

All statements, information, and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee of fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility. No freedom to use any patent owned by INEOS, its subsidiaries, or its suppliers is to be inferred.

