

DERAKANE™ SIGNIA™ RESINS

UNCHANGED PERFORMANCE

Introduction

Introduced in 1965 to combat corrosion in hot, wet chlorine environments, Derakane™ epoxy vinyl ester resins have become the industry standard for corrosion-resistant fiber reinforced polymer (FRP) equipment. High performing derivatives have been introduced over the years to allow vinyl ester solutions for expanded chemical environments, high temperature performance and areas requiring improved toughness. With the introduction of Derakane™ Signia™, INEOS Composites has leveraged new production capabilities to modernize resin features including improved environmental performance, better workability, and increased worker satisfaction.

Features

Derakane™ Signia™ resins provide significant advantages for fabricators, design engineers and asset owner/end users of corrosion-resistant FRP equipment.

In the Shop

- Low styrene emission
- Improved shop efficiency
- Longer shelf life

In the Field

- Consistent polymer backbone
- Identifiable resin system

In this paper, we will expand on the unchanged performance and consistent polymer backbone of Derakane™ Signia™ resins. Derakane™ Signia™ 411 bisphenol-A epoxy vinyl ester resin is used in key examples to demonstrate the polymer backbone is unchanged compared to previous generations of Derakane™ 411. It provides resistance to a wide range of acids, alkalis, bleaches and organic compounds used in chemical processing industry applications.

Assurance of corrosion performance is critical to users and specifiers of FRP equipment. Since the Derakane™ Signia™ polymer backbone is the same compared to previous Derakane™ products, asset owners and engineers can be assured that all previous Derakane™ corrosion studies, historical data and field case histories remain relevant to demonstrate performance for their design requirements. This, combined with improvements for the fabricator, leads to the availability of better, more efficiently produced and more environmentally friendly FRP equipment.

Unchanged Polymer Backbone

Through direct chemical structure evaluation, INEOS verifies the Derakane™ Signia™ 411 polymer backbone is unchanged compared to previous versions of Derakane™ 411 resins. The structure of the resin polymer backbone is proprietary; however, several properties of the Derakane™ Signia™ resin have been evaluated to validate the polymer backbone has not changed. The first step towards this is comparing thermal and mechanical properties and validating they are the same for Derakane™, Derakane™ Momentum™ and Derakane™ Signia™ bisphenol-A epoxy vinyl ester resins. Properties such as tensile and flexural strength, modulus and heat distortion temperature directly measure the characteristics of the cured polymer matrix crosslinking.

Table 1 presents thermal and mechanical properties for cured clear castings of Derakane™ Signia™ 411, Derakane™ 411-350 and Derakane™ Momentum™ 411-350. Taking standard deviation into account for each of the test methods, it can be said that the thermal and mechanical properties for the three resins are the same.^{1,2}

| Property of Casting | Derakane™ Signia™ 411 | Derakane™ 411-350 | Derakane™ Momentum™ 411-350 | Unit (SI) | Method |
|-----------------------------|-----------------------|-------------------|-----------------------------|-----------|-----------|
| Tensile Strength | 85.6 | 81.3 | 83.6 | MPa | ASTM D638 |
| Tensile Modulus | 3.1 | 3.0 | 3.0 | GPa | ASTM D638 |
| Tensile Elongation | 5.1 | 5.1 | 5.2 | % | ASTM D638 |
| Flexural Strength | 147.9 | 138.6 | 144.8 | MPa | ASTM D790 |
| Flexural Modulus | 3.3 | 3.2 | 3.3 | GPa | ASTM D790 |
| Heat Distortion Temperature | 105 | 105 | 105 | °C | ASTM D648 |

Table 1. Typical mechanical properties of Derakane™ Signia™ 411, Derakane™ 411 and Derakane™ Momentum™ 411 clear castings. All properties were calculated on a clear casting that was cured for 24 hours at ambient conditions, then post cured.

Resin viscosity and density are largely governed by polymer chain length and the percent of monomer (styrene) present. In Table 2, the viscosity of Derakane™ Signia™, Derakane™ Momentum™ and Derakane™ 411 family resins are presented. The data shows the viscosity, styrene content and density are the same for all of the resins. If there was a difference in polymer chain construction for these resins, more styrene would be needed for longer average chain lengths, or less styrene for shorter average chain lengths, to achieve the same viscosity. Variations in polymer chain construction would create differences in mechanical properties – which is not seen in Table 1 data.

| Property at 25 °C (77 °F) | Derakane™ Signia™ 411 | Derakane™ 411-350 | Derakane™ Momentum™ 411-350 | Unit (SI) | Method |
|---------------------------|-----------------------|-------------------|-----------------------------|-----------|------------|
| Brookfield Viscosity | 350 | 350 | 350 | cps | ASTM D2196 |
| Styrene Content | 44 | 44 | 44 | % | |
| Density | 1.046 | 1.046 | 1.046 | g/ml | ASTM D1475 |

Table 2. Typical liquid properties of Derakane™ Signia™ 411, Derakane™ 411 and Derakane™ Momentum™ 411 resins.

To confirm corrosion performance is unchanged, Derakane™ Signia™ and classic Derakane™ resins were evaluated in two relatively aggressive chemical environments. Hydrochloric acid and sodium hydroxide are bookends of conditions found in many industrial applications such as chemical manufacturing and mineral processing – consistent performance in these environments is critical and is a key indicator of a consistent polymer backbone.




Figure 1. ASTM C581 corrosion study data for 32% hydrochloric acid at 66 °C (left) and 10% sodium hydroxide at 93 °C (right).

The graphs of C581 corrosion data in Figure 1 show the percent retention of ASTM C581 coupon flex modulus after exposure to 32% hydrochloric acid at 66 °C (150 °F) (Figure 1, left) and after exposure to 10% sodium hydroxide at 93 °C (200 °F) (Figure 1, right). Laminate modulus is determined primarily by the reinforcement, not the resin. The retention of modulus relates directly to degradation of glass reinforcement and the ability of the resin to protect the glass from the chemical environment.² The data demonstrates that the performance between Derakane™ Signia™ and classic Derakane™ bisphenol-A epoxy vinyl ester resins is similar – taking variations inherent to ASTM C581 testing into account.

It should be noted 10% sodium hydroxide at 93 °C (200 °F) is relatively aggressive and the coupon construction chosen is not what would be recommended for this service in a real-world application. This construction was chosen to better evaluate how each resin protects glass reinforcement from chemical attack.³

Summary

The chemistry of epoxy vinyl ester resins makes them highly reactive; when first invented, they were unstable and difficult to use. Introduction of better production capabilities improved their stability and allowed them to become a material of choice for corrosion applications where alloys could not perform. In Derakane™ Signia™ resins, INEOS Composites has combined the best technological features of the Derakane™ and Hetron™ lineage with additional new learnings to introduce a leap forward in stability and usability compared to previous generations of epoxy vinyl ester resins. Liquid, thermo-mechanical and corrosion performance data presented in this paper supports that Signia™ resins deliver unchanged performance within a consistent polymer backbone – assuring customers the vast library of Derakane™ corrosion and case history data collected over the past 50-plus years applies to Signia™ resins.

¹ Clear castings of 3.2 mm (1/8") thickness were prepared between glass plates using standard preparation methods. The castings were cured at room temperature for 24 hours, then post cured. Thermal and mechanical properties were determined using ASTM methods and Instron mechanical testing equipment.

² Properties are typical values based on material tested in our laboratories. Results may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

³ Derakane™ Resin Selection Guide, pp. 8, 65, Spring 2017, INEOS Composites, Dublin, Ohio, 43017.

Global Headquarters
INEOS Composites

North America
Dublin, OH USA
Tel: +1 614 790 9299

Regional Centers

Asia Pacific
Shanghai, P.R. China
Tel: +86 21 2402 4688

Europe
Barcelona, Spain
Tel: +34 93 206 5120

India
Mumbai
Tel: +91 22 6148 9696

Latin America
Araçariquama, Brazil
Tel: +55 11 4136 6477

ineos.com/composites

® Registered trademark, INEOS or its subsidiaries, registered in various countries

™ Trademark, INEOS or its subsidiaries, registered in various countries

© 2019, INEOS / COM19-134W5

All statements, information, and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee of fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility. No freedom to use any patent owned by INEOS, its subsidiaries, or its suppliers is to be inferred.