



## PRODUCT DATA SHEET

## SODIUM SULFITE SOLUTION (15%)

**CAS NO. 7757-83-7**

---

### CHEMICAL COMPOSITION

Sodium Sulfite, wt. %  
Sodium Sulfate, wt. %  
pH

### SPECIFICATION

15 ± 1  
1.0 max  
8.0 – 10.0

---

### PHYSICAL PROPERTIES

Specific Gravity @ 25 ° C  
Density, lbs. /gal @ 25 ° C

1.13 – 1.20  
9.4 – 10.0

---

**DELIVERY MODE:** Stainless steel tank truck.

---

### PRODUCT SAFETY INFORMATION

Avoid contact with skin or eyes as sodium bisulfite is acidic and may cause irritation. Use safety goggles, protective clothing and rubber gloves when handling to minimize contact. Wash thoroughly after handling. In case of eye contact, flush thoroughly with water and call a physician. Flush all parts of body contacted with copious amounts of water. Use only in well ventilated area.

---

### APPLICATIONS INCLUDE:

- Dechlorination in municipal wastewater, pulp & paper, power, and textile water treatment plants
- Boiler water treatment
- Oxygen scavenger
- Preservative
- Pharmaceuticals
- Flue gas desulfurization
- Chemical manufacturing in the sulfonation process

**INEOS CALABRIAN CORPORATION**  
**5500 STATE HIGHWAY 366 PORT NECHES, TX 77651**  
**Phone: (409) 727-1471**  
**PLEASE DIRECT ALL SALES INQUIRIES BY:**  
**Phone: (281) 348-2303 or E-mail: [ContactUs@CalabrianCorp.com](mailto:ContactUs@CalabrianCorp.com)**

The information herein is believed to be reliable. However, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose or as to the merchantability or fitness for a particular purpose and the manufacturer hereby expressly waives any and all such warranties. Further, the manufacturer shall not be liable for damages to person or property arising from or relating to the use, handling, or storage of Product unless damage is due to the manufacturer's negligence or willful misconduct. The manufacturer shall not be liable for damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.