

INEOS Oligomers

Sales Specification

Indopol[®] Polybutene Grade: H-15

SPECIFICATION PROPERTIES	METHOD	ASTM Number	VALUE
Viscosity (mm ² /s) Min Max Temp (°C)	Kinematic Viscosity	D445	27.5 33.5 100
Color (Pt-Co), max	Platinum-Cobalt Scale	mod.D1209	50
Flash Point (°C), min	Pensky-Martens Closed Cup	D93	115
Water (ppm), max	Coulometric Karl Fischer Titration	E1064 ¹	40
Appearance	Visual Inspection	D4176	Clear & Bright

¹ASTM D6304 also acceptable

For user reference, 1 mm²/s = 1 cSt



Technical information contained herein is furnished without charge or obligation, and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, INEOS makes no representation about, and is not responsible or liable for the accuracy or reliability of data, nor for toxicological effects or Industrial Hygiene requirements associated with particular uses of any product described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item not supplied by INEOS. The "Properties" and "Applications" listed in this document are not specifications. They are provided as information only and in no way modify, amend, enlarge, or create any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED.

The name INEOS is a trademark of INEOS Capital Limited.
April, 2018