

Section 1 - Product and Company Identification					
<b>Product Name:</b>		Sulfur Dioxide			
<b>Chemical Formula</b>		SO <sub>2</sub>			
<b>CAS Number:</b>		007446-09-5			
<b>General Use:</b>		Chemical feedstock, food preservative, fumigating pesticide.			
<b>Other Designations:</b>		Sulfurous acid anhydride, sulfurous anhydride, sulfurous oxide.			
<b>Manufacturer:</b>		INEOS Calabrian Corporation 5500 Hwy. 366 Port Neches, Texas 77651			
<b>Telephone:</b>	409-727-1471	<b>Fax:</b>	409-727-5803	<b>Emergency Contact:</b>	CHEMTREC 800-424-9300

Section 2 – Hazard Identification		
<b>GHS Classification</b>	Gases under pressure (Liquefied Gas) Acute Toxicity, Inhalation (Category 3) Skin Corrosion (Category 1B) Serious Eye Damage (Category 1)	<b>Hazard Statement</b>  <b>H280</b> – Contains gas under pressure; may explode if heated. <b>H314</b> – Causes severe skin burns and eye damage. <b>H331</b> – Toxic if inhaled.
<b>Symbol(s):</b>	  	<b>Signal Word:</b>  <b>DANGER</b>
<b>NFPA Rating</b>	<b>Precautionary Statement</b>	
Health Hazard – 3 Fire – 0 Reactivity – 0	<b>P260</b>	Do not breathe gas
	<b>P261</b>	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
	<b>P264</b>	Wash skin thoroughly after handling
	<b>P271</b>	Use only outdoors or in a well-ventilated area.
	<b>P280</b>	Wear Protective gloves/ protective clothing/ eye protection/ face protection.
	<b>P301 + P330 + P331</b>	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	<b>P303 + P361 + P353</b>	IF ON SKIN (or Hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
	<b>P304 + P340 + P310</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
	<b>P305 + P351 + P338 + P310</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
	<b>P363</b>	Wash contaminated clothing before reuse.
<b>P403 + P233</b>	Store in well ventilated place. Keep container tightly closed.	
<b>P405</b>	Store locked up.	

<b>P410 + P403</b>	Protect from sunlight. Store in a well-ventilated place.
<b>P501</b>	Dispose of contents/ container to an approved waste disposal plant.

<b>Other Hazards</b>	Sulfur dioxide is a liquid under pressure.
----------------------	--

### Section 3 – Composition / Information on Ingredients

Composition	CAS Number	% Wt
Sulfur Dioxide	007446-09-5	100
Ingredient	CAS Number	% Wt
Sulfur	007704-34-09	50
Oxygen	007782-44-7	50

### Section 4 – First Aid Measures

<b>General Advice:</b>	Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.
<b>Inhalation:</b>	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
<b>Eye:</b>	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.
<b>Skin:</b>	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.
<b>Ingested:</b>	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### Section 5 - Fire-Fighting Measures

<b>Flash Point:</b>	N/A	<b>Flammability Classification:</b>	Not Flammable
<b>Flash Point Method:</b>	N/A	<b>UEL:</b>	N/A
<b>Burning Rate:</b>	N/A	<b>LEL:</b>	N/A
<b>Auto Ignition Temperature:</b>	N/A		
<b>Extinguishing Media:</b>	Use extinguishing agent appropriate for surrounding fire conditions.		
<b>Unusual Fire or Explosion Hazards:</b>	None Indicated		
<b>Hazardous Combustion Product:</b>	May release hazardous gas.		
<b>Fire-Fighting Instructions:</b>	Do not release runoff from fire control methods to sewers or waterways.		

<b>Fire-Fighting Equipment:</b>	Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full-face piece operated in pressure-demand or positive-pressure mode.
---------------------------------	---

**Section 6 – Accidental Measures**

<b>Spill / Leak Procedures</b>	Wear appropriate PPE - See Section 8
<b>Small Spills / Leaks</b>	Spills can be neutralized with an alkaline material such as caustic soda. Leaks may be located by spraying the area with ammonium hydroxide solution which forms a white fume in the presence of sulfur dioxide.
<b>Large Spills / Leaks</b>	Large spills should be handled according to a predetermined plan. Reduce vapor with fog or fine water spray
<b>Containment</b>	For large spills, dike far ahead of contaminated runoff for later disposal.

**Section 7 - Handling and Storage**

<b>Handling Precautions:</b>	Avoid contact with product
<b>Storage Requirements:</b>	Avoid heat or moisture. Store in properly designed pressure vessels, away from heat and protected from physical damage. Segregate from combustible materials.

**Section 8 - Exposure Controls / Personal Protection:**

<b>Component:</b> SULFUR DIOXIDE		<b>CAS Number:</b>		007446-09-5			
<b>ACGIH (TLV)</b>		<b>OSHA (PEL)</b>			<b>NIOSH (REL)</b>		
<b>STEL</b>	0.25 ppm, 15 Minutes	<b>TWA</b>	5 ppm, 8 Hours	<b>TWA</b>	2 ppm, 10 hours	<b>STEL</b>	5 ppm, 15 min.
		<b>TWA</b>	13 mg/m <sup>3</sup> , 8 hours	<b>TWA</b>	5 mg/m <sup>3</sup> , 10 hours	<b>STEL</b>	13 mg/m <sup>3</sup> , 15 min.
<b>IDLH-</b>	100 ppm	<b>Engineering Controls:</b>		<b>Respiratory Protection:</b>			
<b>IDLH</b> - Immediately Dangerous to Life or Health <b>PEL</b> – Permissible Exposure Limit <b>REL</b> – Recommended Exposure Limit <b>TLV</b> – Threshold Limit Value		Provide general or local exhaust ventilation systems to maintain airborne concentrations below safe exposure limits as stated above. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at the source.		Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.			

<p>ACGIH – American Conference of Governmental Industrial Hygienists TWA – Time Weighted Average based on 8 hour exposure days and a 40 hour week.</p>		
<p><b>Protective Clothing / Equipment:</b> Wear protective gloves, boots, and clothing to prevent prolonged or repeated skin contact. Wear protective eyeglasses or goggles, per OSHA eye and face protection regulations (29 CFR 1910.133).</p>	<p><b>Safety Stations:</b> Make emergency eyewash stations, showers, and washing facilities available in the work area</p>	<p><b>Contaminated Equipment:</b> Separate contaminated work clothes from street clothes. Remove this material from shoes and clean personal protective equipment.</p> <p><b>Comments:</b> Do not eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before food or beverage consumption.</p>

**Section 9 - Physical and Chemical Properties**

<b>Physical State:</b>	Liquid / Gas	<b>Water Solubility:</b>	11g/100g H2O NA
<b>Appearance:</b>	Colorless	<b>Other Solubility:</b>	
<b>Odor Threshold:</b>	0.5 ppm;	<b>Boiling Point:</b>	14° F
<b>Vapor Density (Air=1):</b>	2.26	<b>Freezing Point:</b>	-104° F
<b>Vapor Pressure:</b>	2432 mm HG @ 68° F	<b>Melting Point:</b>	-98.9° F
<b>Density:</b>	N/A	<b>Evaporation Rate:</b>	Rapid
<b>Specific Gravity (H2O=1):</b>	1.434	<b>pH:</b>	Acidic
<b>Molecular Weight:</b>	64.07	<b>% Volatile</b>	N/A

**Section 10 - Stability & Reactivity**

<b>Stability:</b>	Stable under normal conditions.
<b>Polymerization:</b>	Hazardous polymerization will not occur.
<b>Chemical Incompatibilities:</b>	Contact with powdered potassium, sodium metal oxidizing agents produce violent reactions. Reacts with water and steam to form corrosive sulfuric acid. Reacts with chlorates to form unstable chlorine dioxide.
<b>Conditions to Avoid:</b>	Avoid excessive heat, or open flame.
<b>Hazardous Decomposition Products:</b>	May release hazardous gas.

**Section 11 - Toxicological Information**

<b>Eye Effects (rabbit):</b>	Mild (6 ppm/4H/32D)	<b>Acute Inhalation Effects (rat):</b>	LC50=2520 ppm (1H0)
<b>Skin Effects (rabbit):</b>	Not available	<b>Acute Oral Effects (rat):</b>	Not available
<b>Carcinogenicity:</b>	IARC, NTP, and OSHA do not list Sulfur Dioxide as a carcinogen.		
<b>Chronic Effects:</b>	Prolonged or repeated exposure may cause inflammation of the lining of the nose, dry throat and cough. Respiratory tract symptoms have been observed similar to changes observed in human chronic bronchitis.		

**Section 12 - Ecological Information**

<b>Ecotoxicity:</b>	Sulfur Dioxide is a poisonous gas commonly used as a fumigant pesticide. Concentrations above 1 ppm are believed to be injurious to plant foliage.
<b>Environmental Transport:</b>	Airborne gas
<b>Environmental Degradation:</b>	Rapid evaporation.
<b>Soil Absorption/Mobility:</b>	Slight.

**Section 13 - Disposal Considerations**

<b>Disposal:</b>	Waste determinations typically consider Sodium Metabisulfite contaminated to be non-hazardous.	<b>Container Cleaning and Disposal:</b>	Follow applicable Federal, state and local regulations.
------------------	--	---	---

**Section 14 - Transport Information**

<b>Shipping Name:</b>	Sulfur Dioxide
<b>Shipping Symbols:</b>	
<b>Hazard Class:</b>	2.3
<b>Subsidiary Hazard:</b>	8
<b>ID No. (Placard):</b>	UN 1079
<b>Packing Group:</b>	N/A
<b>Label:</b>	Poison Gas
<b>EPA Reportable Quantity (RQ):</b>	500 pounds

**Section 15 - Regulatory Information**

**EPA Regulations:**

<b>RCRA Hazardous Waste Classification (40 CFR 261):</b>	D002.	<b>FIFRA:</b>	Regulated when used as a pesticide
<b>CERCLA Hazardous Substance (40 CFR 302.4):</b>	Not Listed	<b>SARA Title III:</b>	Section 302/304/311/312 Extremely Hazardous Substance: sulfur dioxide, 500 TPQ Section 302/304 Emergency Planning and Notification: sulfur dioxide, 500 RQ
<b>CERCLA Reportable Quantity (RQ):</b>	Not Listed		

**OSHA Regulations:** Air Contaminant (29 CFR 1910.1000): Listed without ceiling or skin designation.

**OSHA Specifically Regulated Substance:** : List of Highly Hazardous Chemicals TQ=1000 lb

<b>Other Regulations:</b>	<p>FDA: Regulated when used as a food preservative.          Proposition 65 (California): Listed as a reproductive toxicant.          Canada:          WHMIS           A - Compressed gas                                D1A - Causing immediate and serious toxic effects                                E - Corrosive material          CEPA            Listed in Canadian Environmental Protection Administration Toxic Substance List.          NPRI             Listed in Canadian National Pollutant Release Inventory</p>
---------------------------	--

**Section 16 - Other Information**

**This product is NSF certified to NSF/ANSI Standard 60 and is subject to maximum use limit (MUL) of 10 mg/L for potable water dechlorination application**

<b>Previous SDS issue date:</b>	June 2, 2021
<b>Current SDS issue date:</b>	September 23, 2021
<b>Reason for current revision</b>	NFS Certification – Section 16

The information herein is believed to be reliable. However, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer shall not be liable for damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.